



QTH32

DVR Technology	BNC HD
Channels	32
Recording Resolution	1080p, 720p, 960H
Live Viewing Resolution	1080p / 720p / 1280x1024 / 1024x768 / 800x600
Live Display FPS	15 FPS per Channel (1080p) 30 FPS per Channel (960H/720p)
Hard Drive	Supports 8 HDD up to 6TB each
Remote Monitoring	10 Simultaneous Users
Compatibility	Mac and PC
Connects With	Local Cameras
Monitor Connections	HDMI, VGA



**Supports QTH BNC HD Cameras
& Analog Cameras**

DVR

Video Compression	H.264
Live Display Resolution	1080p, 720p, 1280x1024, 1024x768, 800x600
Live Display FPS	1080p @15 FPS / 720P-960H @30FPS
Display Modes	1, 4, 8, 16, 32 Auto Sequence
Languages	English, Chinese (Simplified & Traditional), Czech, French, Portuguese, Spanish, Turkish, Bulgarian, Greek, Italian, German, Russian, Polish, Japanese, Indonesian, Thai, Hungarian, Lithuanian, Vietnamese, Dutch, Swedish, Norwegian, Persian, Arabic, Romanian

RECORDING RESOLUTION OPTIONS

1080p Resolution	1920 x 1080 pixels
720P Resolution	1280 x 720 pixels
960H Resolution	960 x 480 pixels

RECORDING MODES

Recording Modes	Manual, Time Schedule, Motion Detection, Sensor
Backup Methods	PC, Flash, USB Hard Drive

PLAYBACK ON DVR

Playback Speed	1080p at 15 FPS per channel	480 FPS total
	720P at 30 FPS per channel	960 FPS total
	960H at 30 FPS per channel	960 FPS total
Number Channels	8 Simultaneous Local Playback	

REMOTE MONITORING

Scan 'N View	Yes
Dual Stream	CIF
Simultaneous Users	10

COMPATIBILITY

Software Support	QT View
Mobile Support	iPhone, iPad, Android
Computer Support	WinXP, Vista, Win7/8/10 Mac OS 10.7-10.11
Cameras Support	QTH Series / QTA Series / Analog

VIDEO, AUDIO & ALARM PORTS

Video In	32 BNC
Video Out	HDMI, VGA
Alarm In	16
Alarm Out	4
Audio In	16 RCA
Audio Out	1 RCA

COMMUNICATION PORTS

Network	RJ45 10/100 Mbps
USB	2 USB 2.0
eSATA	2

ACCESSORIES

Control	USB Mouse, Remote Control
Connectors / Cables	HDMI Cable
Mounting Hardware	Screws for Hard Drives
Other	Quick Start Guide

(QTH32 cont'd...)

HARD DRIVES

Maximum Size	6TB
Number Supported	8

PTZ

PTZ Support	RS485
Supported Protocols	COC, Null, Pelco D, Pelco P, Lilin, Minking, Neon, Star, VIDO, DSCP, VISCA, Samsung, RM110, HY

POWER

Power Supply	110-240V
Power Consumption	40w (w/o HD)

PHYSICAL

Weight	14.4 lbs
Dimensions	16.75"W X 17.75"D X 3.5"H
Operating Temperature	32°– 122°F

